

Learning Invariants and Representation Spaces of Shapes and Forms

Ron Kimmel




Geometric Image Processing Lab.

Technion - Israel Institute of Technology




SIAM AM July 13 2018

Manifold vs. Riemannian Manifold



Planar Curves




$$C(p) : [0, 1] \in \mathbb{R}^1 \rightarrow \mathbb{R}^2$$

$$C(p) = \{x(p), y(p)\} \quad p \in [0, 1]$$

Arc-length and Curvature


$$s(p) = \int_0^p |C_{\hat{p}}| d\hat{p} \quad \Rightarrow \quad |C_s| = 1, \quad \left(\vec{t} = C_s = \frac{C_p}{|C_p|} \right)$$



Linear Transformations


Affine: $\{\tilde{x}, \tilde{y}\}^T = A\{x, y\}^T + \bar{b},$

Euclidean: $A = [\bar{u}_1, \bar{u}_2],$ where $\langle \bar{u}_1, \bar{u}_2 \rangle = 0$ and $\langle \bar{u}_i, \bar{u}_i \rangle = 1.$




Linear Transformations

Equi-Affine: $\{\tilde{x}, \tilde{y}\}^T = A\{x, y\}^T + \bar{b}, \quad \det(A) = 1.$




Differential Signatures

- Euclidean invariant signature $\{s, \kappa\}$





Differential Signatures


- Euclidean invariant signature $\{s, \kappa\}$



Learning invariants




Robustness to noise




Differential Signatures

- Euclidean invariant signature $\{\kappa(s), \kappa_s(s)\}$



Euclidean arclength

- Length is preserved, thus
$$\begin{aligned} 1 &= \langle C_s, C_s \rangle \\ &= \langle C_p p_s, C_p p_s \rangle \\ &= \langle C_p, C_p \rangle p_s^2 \end{aligned}$$




$$ds^2 = \langle C_p, C_p \rangle dp^2$$

$$ds = |C_p| dp$$

Equi-affine arclength

- Area is preserved,



$$1 = (C_v, C_{vv})$$

$$= (C_p p_v, \frac{d}{dp} (C_p p_v) p_v)$$

$$= (C_p, C_{pp} p_v + C_p \frac{d}{dp} p_v) p_v^2$$

$$= (C_p, C_{pp} p_v) p_v^2$$


$$= (C_p, C_{pp}) p_v^3$$

$$dv = (C_p, C_{pp})^{1/3} dp = (C_s, C_{ss})^{1/3} ds = |\kappa|^{1/3} ds$$

Scale inv. arclength


- Ratio is preserved,

$$\begin{aligned} 1 &= \frac{|C_\theta|}{\rho} \\ &= \kappa |C_\theta| \\ &= \kappa |C_p p_\theta| \\ &= \kappa |C_p| p_\theta \end{aligned}$$



$$d\theta = \kappa |C_p| dp = \kappa ds$$

Scale invariance?



$$d\theta = |\kappa| ds$$


From curves to surfaces

$$K = \kappa_1 \kappa_2$$

$$S(u, v) = \begin{pmatrix} x(u, v) \\ y(u, v) \\ z(u, v) \end{pmatrix}$$

$$dx^2 = (x_u du + x_v dv)^2 = x_u^2 du^2 + 2x_u x_v du dv + x_v^2 dv^2$$

$$\begin{aligned} ds^2 &= dx^2 + dy^2 + dz^2 \\ &= (du \ dv) \begin{pmatrix} S_u^2 & \langle S_u, S_v \rangle \\ \langle S_u, S_v \rangle & S_v^2 \end{pmatrix} \begin{pmatrix} du \\ dv \end{pmatrix} \\ &= (du \ dv) \begin{pmatrix} g_{11} & g_{12} \\ g_{21} & g_{22} \end{pmatrix} \begin{pmatrix} du \\ dv \end{pmatrix} \end{aligned}$$




From curves to surfaces

$$\begin{aligned}
 d\tilde{s}^2 &= \kappa_1 \kappa_2 (dx^2 + dy^2 + dz^2) \\
 &= (du \, dv) \begin{pmatrix} K S_u^2 & K \langle S_u, S_v \rangle \\ K \langle S_u, S_v \rangle & K S_v^2 \end{pmatrix} \begin{pmatrix} du \\ dv \end{pmatrix} \\
 &= (du \, dv) (K g_{ij}) \begin{pmatrix} du \\ dv \end{pmatrix}
 \end{aligned}$$



Karl Friedrich Gauss




$$\tilde{g}_{ij} = |K| g_{ij} = |\kappa_1 \kappa_2| \langle S_i, S_j \rangle$$


Farthest Point Sampling - Voronoi

$$g_{ij} = \langle S_{\omega_i}, S_{\omega_j} \rangle$$

$$\tilde{g}_{ij} = |K| \langle S_{\omega_i}, S_{\omega_j} \rangle$$




Regular
metric




Scale invariant
metric

Generalized MDS




Regular metric

$$g_{ij} = \langle S_{\omega_i}, S_{\omega_j} \rangle$$



$$\tilde{g}_{ij} = |K| \langle S_{\omega_i}, S_{\omega_j} \rangle$$

Scale invariant metric



Surface Laplacian

$$\Delta_{\tilde{g}} \equiv -\frac{1}{\sqrt{\tilde{g}}} \partial_i \sqrt{\tilde{g}} \tilde{g}^{ij} \partial_j$$



$$\tilde{g}_{ij} = \text{[Composite Image of Two Men]} = |\kappa_1 \kappa_2| \langle S_i, S_j \rangle$$

Regular metric $g_{ij} = \langle S_{\omega_i}, S_{\omega_j} \rangle$

$\Delta_g \phi_i = \lambda_i \phi_i$ Eigenfunctions



Scale invariant metric $\tilde{g}_{ij} = |K| \langle S_{\omega_i}, S_{\omega_j} \rangle$



$\Delta_g \phi_i = \lambda_i \phi_i$ Eigenfunctions





How could we
use algebra to
describe geometry?

René Descartes




Yann LeCun



Geoff Hinton

Functional Maps Ovsjanikov et al. 2012



Functional Maps Ovsjanikov et al. 2012



$\{\psi_i\}$

$$f = \sum_i \langle f, \psi_i \rangle \psi_i = \sum_i \alpha_i \psi_i$$



$\{\phi_i\}$

$$f = \sum_i \langle f, \phi_i \rangle \phi_i = \sum_i \beta_i \phi_i$$

$$\beta = C\alpha$$

$$C_{ij} = \langle T(\phi_i), \psi_j \rangle$$

Functional Maps



$\{\psi_i\}$

$$f = \sum_i \langle f, \psi_i \rangle \psi_i = \sum_i \alpha_i \psi_i$$








$\{\phi_i\}$

$$f = \sum_i \langle f, \phi_i \rangle \phi_i = \sum_i \beta_i \phi_i$$

$$\beta = C\alpha$$

$$C_{ij} = \langle T(\phi_i), \psi_j \rangle$$

Self functional maps



Eigenfunctions


$$g_{ij} = \langle S_{\omega_i}, S_{\omega_j} \rangle$$

$$-\Delta_g \psi_i = \lambda_i \psi_i$$








$$\tilde{g}_{ij} = |K| g_{ij}$$


$$-\Delta_{\tilde{g}} \tilde{\psi}_i = \tilde{\lambda}_i \tilde{\psi}_i$$





Isometry classes














input 2D image



output 3D face




output 3D face
with texture


*Thank you for
your attention*



Our domain



Coded light 3D scanner






Intel REALSENSE™
TECHNOLOGY



$$\iiint dx dt dS$$



RealSense
refined
via SfS

$$I = \rho \langle \vec{l}, \vec{N} \rangle$$



Alex




Michael

Alexander



Michael

Face recognition challenges



Is this the same person?

Face decomposition



=




PHOTOMETRY
(2D)

+



GEOMETRY
("3D")

Expressions $\approx$ Isometries



- Extrinsic (Euclidean) geometry = expressions
- Intrinsic (Riemannian) geometry = identity

Most models have exceptions



from youtube

$$\inf_{\varphi: S \rightarrow Q} |d_Q(\varphi(s), \varphi(s')) - d_S(s, s')|$$


Morphing

Texture




$$(1 - \lambda)S + \lambda Q$$

Remarkable result



Tsao Lab / Caltech

Caltech



Facial images can be linearly reconstructed using responses of ~200 face cells

Chang & Tsao The code for facial identity in the primate brain. *Cell*, 2017

3DMM



Vetter & Blanz, A morphable model for the synthesis of 3D faces, Siggraph 1999
Kemelmacher & Basri, 3D face reconstruction from a single image ... PAMI 2011

Learning using Axiomatic Knowledge




Learning using Axiomatic Knowledge




Learning using Axiomatic Knowledge

We know how to model faces



Can we use that to learn the inverse problem?



Face reconstruction evolution



3DMM

CNN
I → 3DMM

3DMM
to Z

SfS
Z2z



3DMM

CNN
I → 3DMM

3DMM
to Z

SfS

CNN
Z2z




3DMM



CNN
I → Z


SfS

CNN
Z2z



More results





input 2D image



output 3D face



output 3D face
with texture

Analyzing Facial Expressions

- 1800s - Charles Bell, Duchenne de Boulogne
- Darwin - Expressions as an evolutionary mechanism



AU 10+12+
16+25



AU 22+25+26



AU 12+25+26



AU 6+10+
12+16+25+27



AU 17+24



Bared-teeth



Pant-hoot



Play face




Scream



Bulging-lip face

Universal Expressions & Emotions




Universal Expressions & Emotions

- Joy (Happiness)
- Sadness
- Fear
- Disgust
- Anger
- Contempt
- Surprise



Sounds familiar?




Facial Action Coding System

- Ekman & Friesen 1978
- Taxonomized facial movements by appearance based on muscle clusters & contractions


Upper Face Action Units					
AU 1	AU 2	AU 4	AU 5	AU 6	AU 7
Inner Brow Raiser	Outer Brow Raiser	Brow Lowerer	Upper Lid Raiser	Cheek Raiser	Lid Tightener
*AU 41	*AU 42	*AU 43	AU 44	AU 45	AU 46
Lid Droop	Slit	Eyes Closed	Squint	Blink	Wink
Lower Face Action Units					
AU 9	AU 10	AU 11	AU 12	AU 13	AU 14
Nose Wrinkler	Upper Lip Raiser	Nasolabial Deepener	Lip Corner Puller	Cheek Puffer	Dimpler
AU 15	AU 16	AU 17	AU 18	AU 20	AU 22
Lip Corner Depressor	Lower Lip Depressor	Chin Raiser	Lip Puckerer	Lip Stretcher	Lip Funneler
AU 23	AU 24	*AU 25	*AU 26	*AU 27	AU 28
Lip Tightener	Lip Pressor	Lips Part	Jaw Drop	Mouth Stretch	Lip Suck

W/O Macaque Monkeys

What can be said about expressions?



W/O macaque monkeys



Visualizing CNN Filters



Breuer & K. A deep learning perspective on the origin of facial expressions, BMVC/workshops 2017

*Thank you for
your attention*

